DisplayPort to VGA Adapter

BCP161

Article Information

Product Group:	MULTIMEDIA
Sub Group:	ADAPT/PLUG
Article group:	DISPLAYPORT
Date of introduction:	August 2010
Number:	BCP161
Product Name:	DisplayPort to VGA Adapter
Usage:	Connect your computer with DisplayPort to a screen with VGA input

Features & Benefits

DisplayPort 1.1a compliant receiver offering 5.4 Gbps bandwidth over 2 lanes
Integrated triple 10-bit, 162 MHz video DAC for analogue VGA signal output
Supports up to 1080p, 1920 x 1200 reduced blanking video resolution
EDID (Extended Display Identification Data) pass-through from PC source to display
Spread Spectrum (de-spreading) for EMI reduction
Automatic sink detection
Low power standby mode operation initiated based on sink detection status
Powered from DisplayPort source
3.3V IO, 1.2V Core
Low power operation – Active 400mW, standby mode 15mW

Technical Information

Length:	0,2 m / 0.7 ft
From Connector:	DisplayPort Male
To Connector:	HD15 VGA Female

OFC Cable
Double shielded cable
Nickel Plated Contacts
Moulded DisplayPort plug

System Requirements

Monitor or screen with VGA input
VGA Cable
Computer/Notebook with DisplayPort output

Package Contents

DisplayPort to VGA Adapter

Bandridge Europe N.V.
P.O. Box 2333
2301CH LEIDEN
The Netherlands
T: + 31 (0)71 89 00 20 0
F: + 31 (0)71 89 00 20 9
E: sales@bandridge.com
I: bandridgeportal.com

Specifications are subject to change without notice.

Logistical Information

Languages: GB, DE, FR, NL, ES, IT, PT, DK, PL, SE, RU, CZ, HU, TR
Package size: B1F
Qty on display hook: 5 pcs

	Quantity	Packaging (HxDxW)	Weight	Barcode
Product	1 pcs	0,110 x 0,040 x 0,145 m	0,000 Kg	8717587044960
Inner carton	10 pcs	0,000 x 0,000 x 0,000 m	0,000 Kg	8717587044977
Outer carton	80 pcs	0,000 x 0,000 x 0,000 m	0,000 Kg	8717587044984

Bandridge Europe N.V.
P.O. Box 2333
2301CH LEIDEN
The Netherlands
T: + 31 (0)71 89 00 20 0
F: + 31 (0)71 89 00 20 9
E: sales@bandridge.com
I: bandridgeportal.com

Specifications are subject to change without notice.